



Catalog No. 9T40G0008

Description: AL 3P 300KVA 480-208Y/120

UPC No 078317316763

Products > Transformers > Dry Type Vented > General Purpose

GE TransforMore[™] transformers Incorporate fan-assisted cooling so they're much smaller and lighter than traditional transformers. All TransforMore[™] transformers meet NEMA TP-1 efficiency standards. They are available with aluminum or copper windings and utilize a UL recognized 220°C insulation system.

- UL Listed

- Incorporates fan-assisted cooling
- Single-piece front/back is easily removable for service
- NEMA 2 drip-proof enclosure standard; weathershield kit is available for conversion to NEMA 3R outdoor configuration
- Qualified to the seismic requirements of IEEE-693-2005 and IBC-2006
- Copper or aluminum windings
- Copper ground strap
- Robust packaging with top and side protection protects against shipping damage
- 100% factory tested for shorts and coil integrity, current and loss, voltage, impedance and noise.
- Clear, comprehensive documentation and labeling

Descriptors

Category	General Purpose
GO Schedule	TN

Specifications

Phase	3
PriVoltage	480
SecVoltage	208Y/120
KVA	300.0 KVA
Coil Material	AL
TempRise	150.0 °C
ElecShield	Ν
SubType	VENTED
Frequency	60 Hz
Net Weight	1020
TempClass	220.0 °C
AmbTemp	40.0 °C
InsulSys	IS-19C
EnergyEfficiency	NEMA TP 1
KFactor	К1
Enclosure Type	NEMA 2
Net Weight	1020
Fan Cooled	Yes
GSA Compliance	Yes

Classifications

UL	Yes
cUL	No
CE	No

Publications		
Title	Publication No.	Publication Type
9T40G0008 - Transformer Label Drawing		Drawings-Outline and Dimensional
Label drawing in .pdf format	9T40G0008-LBL	
9T40G0008 - Typical Test Data Report		
Typical Test Data Report	9T40G0008	Data Sheets
Transformer Outline Drawing		Drawings-Outline and Dimensional
Outline drawing in .pdf format.	303B899AAP078	

Additional Documentation: Visit our <u>Publication Library</u> to find technical documentation, time current curves, CSI Specifications and promotional literature.